

PVI 50TL & PVI 60TL

3-Ph Transformerless Commercial String Inverters

Features

- Integrated arc fault protection
- Compliant with UL 1741SA
- 3 MPPTs with 5 inputs each
- Integrated DC and AC disconnects
- AC terminals compatible with copper and aluminum conductors
- Modbus communications
- Internal data logger
- 0 - 90° installation orientation
- Remote firmware upgrades
- Remote diagnostics
- Compatible with certain MLPE for module-level rapid shutdown*

Options

- Shade cover
- DC fuse bypass
- Web-based monitoring



Yaskawa Solectria Solar's PVI 50TL and PVI 60TL are grid-tied, transformerless three-phase inverters designed for ground mount, rooftop and carport arrays and can be installed from 0 - 90 degrees. The PVI 50/60TL inverters are the most reliable, efficient and cost effective in their class. They come standard with AC and DC disconnects, three MPPTs, a 15-position string combiner, remote diagnostics, remote firmware upgrades and various protection features. Options include shade cover, DC combiner fuse bypass, and web-based monitoring.

PVI 50TL & PVI 60TL

Specifications

	PVI 50TL	PVI 60TL
DC Input		
Absolute Maximum Input Voltage	1000 VDC	1000 VDC
Maximum Power Input Voltage Range (MPPT)	480-850 VDC	540-850 VDC
Operating Voltage Range (MPPT)	200-950 VDC	200-950 VDC
Maximum Operating Input Current	108 A (36 A per MPPT)	114 A (38 A per MPPT)
Number of MPP Trackers	3	3
Maximum Available PV Current (Isc x 1.25)	204 A (68 A per MPPT)	204 A (68 A per MPPT)
Maximum PV Power	75 kW (30 kW per MPPT)	90 kW (33 kW per MPPT)
Start Voltage	330 V	330 V
AC Output		
Nominal Output Voltage	480 VAC, 3-Ph/PE/N	480 VAC, 3-Ph/PE/N
AC Voltage Range (Standard)	-12/+10%	-12/+10%
PF=1.00 - Real/Apparent Power/Output Current	50 kW / 50 kVA / 60.2 A	60 kW / 60 kVA / 72.3 A
PF=±0.91 - Real/Apparent Power/Output Current	50 kW / 55 kVA / 66.2 A	60 kW / 66 kVA / 79.4 A
Nominal Output Frequency	60 Hz	60 Hz
Output Frequency Range	57-63 Hz	57-63 Hz
Power Factor	Unity, >0.99 (Adjustable 0.8 leading to 0.8 lagging)	Unity, >0.99 (Adjustable 0.8 leading to 0.8 lagging)
Fault Current Contribution (1 Cycle RMS)	55 A	55 A
Total Harmonic Distortion (THD) @ Rated Load	<3%	<3%
Recommended OCPD Device	90 A	100 A
AC Surge Protection	Type II MOV, 1240Vc, 15kA I _{tm} (8/20μ)	
Efficiency		
Peak Efficiency	99.0%	99.0%
CEC Efficiency	98.5%	98.5%
Tare Loss	< 2 W	< 2 W
Integrated String Combiner		
Fused Inputs	15 Fused Positions (5 Positions per MPPT) 15 A Standard (20, 25, 30 A accepted)**	
Temperature		
Ambient Temperature Range	-22°F to +140°F (-30°C to +60°C); Derating occurs over +122°F (+50°C)	
Storage Temperature Range	No low temp minimum to +158°F (+70°C)	
Relative Humidity (non-condensing)	0-95%	
Operating Altitude	13,123 ft (4,000 m) Derating occurs from 9,842.5 ft (3,000 m)	
Communications		
Data Logger Hardware	Standard, Internal	
SolrenView Web-Based Monitoring Service	Optional	
Revenue Grade Metering	Optional, External	
Communication Interface	RS-485 Modbus RTU	
Remote Firmware Upgrades	Standard	
Remote Diagnostics	Standard	
Features & Protections		
Arc-Fault	Standard	
Smart Grid Features	L/HVRT, L/HFRT, Volt-Var, Frequency-Watt and Volt-Watt, Soft-Start, Soft-Step	
Testing & Certifications		
Safety Listings & Certifications	UL 1741SA-2016, UL1699B, CSA-C22.2 #107.1, IEEE1547a-2014	
Advanced Grid Support Functionality	Rule 21, UL 1741SA	
Testing Agency	ETL	
FCC Compliance	FCC Part 15	
Warranty		
Standard Limited Warranty	10 Years	
Enclosure		
Acoustic Noise Rating	< 60 dBA @ 1 m at room temperature	
AC/DC Disconnect	Standard, fully-integrated	
Mounting Angle***	0-90° from horizontal (vertical, angled, flat)	
Dimensions (H x W x D)	39.4 in. x 23.6 in. x 10.2 in (1,000 mm x 600 mm x 260 mm)	
Weight	Inverter: 123.5 lbs (56 kg); Wiring Box: 33 lbs (15 kg)	
Enclosure Rating and Finish	Type 4X; Polyester Powder Coated Aluminum	

*Please inquire about compatible Module-Level Power Electronics (MLPE)

**Yaskawa Solectria Solar does not supply optional fuses sizes

***Shade cover accessory required for installation of 75° or less

SOLECTRIA SOLAR

Yaskawa Solectria Solar

360 Merrimack Street
Lawrence, MA 01843
solectria.com

1-978-683-9700
inverters@solectria.com

DOCR-070642-Q | August 2019
© 2019 Yaskawa Solectria Solar

YASKAWA