



Eliminates The Need For All Other Pulling Ropes

CUSTOM LENGTHS AVAILABLE!



PULL-SLICK™

- An innovative high performance synthetic fiber pulling rope

Strength

- High tensile strength: 39,000 lb.
- 12 Strand single braided synthetic fiber
- Pound for pound stronger than steel
- Ultra low stretch

Speed

- 25% Reduction in coefficient of friction compared to traditional pulling ropes
- 2/3 Lighter than traditional pulling rope

Convenience

- Need only one size rope (9/16") for pulls up to 15,000 lb. pulls
- Does not absorb water
- Dual factory installed pulling eyes, one on either end
- Lightweight

Durable

- Abrasion resistance for less fray
- Will not rot; no organics in rope
- UV resistant



Model	Description	Dia. (IN)	Avg. Breaking Strength	Total Wt.	Dimensions (IN)
PS18-300	1/8" x 300' PullSlick	1/8"	2,800 lb.	8 lb.	12 x 11 x 11
PS14-300	1/4" x 300' PullSlick	1/4"	7,500 lb.	5 lb.	12 x 11 x 11
PS14-600	1/4" x 600' PullSlick	1/4"	7,500 lb.	8 lb.	15 x 15 x 16
PS14-1200	1/4" x 1200' PullSlick	1/4"	7,500 lb.	16 lb.	20 x 20 x 20
PS916-300	9/16" x 300' PullSlick	9/16"	39,000 lb.	45 lb.	17 x 17 x 17
PS916-600	9/16" x 600' PullSlick	9/16"	39,000 lb.	63 lb.	21 x 21 x 17
PS916-900	9/16" x 900' PullSlick	9/16"	39,000 lb.	91 lb.	24 x 24 x 24
PS916-1200	9/16" x 1200' PullSlick	9/16"	39,000 lb.	116 lb.	25 x 25 x 22
PS34-1500	3/4" x 1500' PullSlick	3/4"	83,000 lb.	262 lb.	30 x 30 x 34
PS34-3000	3/4" x 3000' PullSlick	3/4"	83,000 lb.	524 lb.	39 x 39 x 37
PS718-2600	7/8" x 2600' PullSlick	7/8"	90,000 lb.	650 lb.	42 x 35 x 35
PS18-CUST	Custom 1/8" PullSlick Rope (100' to 4900') (Eye on Each End)	1/8"	2,800 lb.	varies	varies
PS14-CUST	Custom 1/4" PullSlick Rope (100' to 4900') (Eye on Each End)	1/4"	7,500 lb.	varies	varies
PS916-CUST	Custom 9/16" PullSlick Rope (100' to 4900') (Eye on Each End) (Over 1200' Comes on Real Spool)	9/16"	39,000 lb.	varies	varies